

CP- UNC-VA30L3S-V2**3MP Full HD IR Vandal Dome Camera - 30Mtr.****Main Features**

- 1/3" 3MP PS CMOS Image Sensor
- Max 20fps@3M(2048×1536)&25/30fps@1080P(1920×1080)
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night (ICR), Auto Iris, 3DNR, AWB, AGC, BLC
- 2.8 mm fixed lens (3.6 mm optional)
- Array Range of 30 Mtrs, IP67, IK10, PoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNC-VA30L3S-V2

3MP Full HD IR Vandal Dome Camera - 30Mtr.



Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Gain Control (AGC)
 Lens
 Back Light Compensation
 S/N Ratio
 Video Compression
 Resolution
 Frame Rate
 Privacy Mask
 ICR
 Protocol
 Ethernet
 User Account
 Smart Phone
 IR
 Operating Temperature
 Power Source
 Power Consumption
 Weatherproof Standard
 Dimension
 Weight

Specification

1/3" 3MP PS CMOS Image Sensor
 0.1Lux/F2.0(Color), 0Lux/F2.0(IR on)
 Auto/Manual, 1/3(4)~1/100000s
 Auto/Manual
 Auto/Manual
 2.8 mm (3.6 mm optional)
 BLC/ HLC/ DWDR
 More than 50dB
 H.264/ H.264H/ MJPEG
 3M(2048×1536)/1080P(1920×1080)/720P(1280×720)/D1(704×576/704×480) /CIF
 (352×288/352×240)
 Main Stream: 3M(1 ~ 20fps)/1080P(1 ~ 25/30fps), Sub Stream :D1(1 ~ 25/30fps)
 Up to 4 areas
 Auto (ICR)/Color/B/W
 IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP,
 DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF, CGI
 RJ-45 (10/100Base-T)
 20 Users
 iPhone, iPad, Android Phone
 IR Range of 30 Mtr.
 -30°C~+60°C , Less than 95%RH
 DC12V, PoE (802.3af)
 <4.5W(IR on)
 IP67 & IK10
 Φ109.9mm × 81mm (4.33" x 3.19")
 0.34kg

