

Share:



AP4423



Description: Provides redundant rack mount power to single-corded equipment.
Includes : Mounting hardware , Rack Mounting brackets , Serial configuration cable

Product Support

- User Manual
- Software & Firmware
- Product Registration
- Product FAQs

Product Overview

Technical Specifications

Documentation

Drawings

Software & Firmware

Options

Output

Print Technical Specification

Nominal Output Voltage	230V
Overload Protection	No
Maximum Total Current Draw	16
Output Connections	(1) IEC 320 C19 (Battery Backup) (8) IEC 320 C13 (Battery Backup)

Input

Nominal Input Voltage	230V
Input frequency	50/60 Hz
Input Connections	IEC-320 C20
Maximum Input Current	20A
Maximum Line Current	20A

Physical

Maximum Height	44mm , 4.4CM
Maximum Width	432mm , 43.2CM
Maximum Depth	236mm , 23.6CM
Rack Height	1U
Net Weight	3.74KG
Shipping weight	5.51KG
Shipping Height	114mm , 11.4CM
Shipping Width	600mm , 60.0CM
Shipping Depth	356mm , 35.6CM
Color	Black

Environmental

Operating Temperature	-5 - 45 °C
Operating Relative Humidity	5 - 95 %

Operating Elevation	0-3000meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0-15000meters
Conformance	
Approvals	cUL Listed, CE, EN 55022 Class A, FCC Part 15 Class A, UL Listed
Standard warranty	2 years repair or replace
Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs
Battery Directive	Compliant
Other Environmental Compliance	China RoHS