

Share:



AP7724



Description: Provides redundant rack mount power to single-corded equipment.  
Includes : Documentation CD , Rack Mounting brackets , RS-232 configuration cable , Warranty card

## Product Support

- User Manual
- Software & Firmware
- Product Registration
- Product FAQs

Product Overview

Technical Specifications

Documentation

Software & Firmware

### Output

Print Technical Specification

Nominal Output Voltage	230V
Overload Protection	Yes
Maximum Total Current Draw	32

Output Connections  
(16) IEC 320 C13 (Battery Backup)  
(2) IEC 320 C19 (Battery Backup)

### Input

Nominal Input Voltage	200V , 208V , 230V
Input frequency	50/60 Hz
Input Connections	IEC 309 32A 2P+E
Cord Length	2.44meters
Number of Power Cords	2
Maximum Input Current	32A
Maximum Line Current	32A

### Physical

Maximum Height	88mm , 8.8CM
Maximum Width	432mm , 43.2CM
Maximum Depth	236mm , 23.6CM
Rack Height	2U
Net Weight	6.86KG
Shipping weight	9.36KG
Shipping Height	216mm , 21.6CM
Shipping Width	589mm , 58.9CM
Shipping Depth	356mm , 35.6CM

### Environmental

Operating Temperature	-5 - 45 °C
-----------------------	------------

Operating Relative Humidity	5 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0-15000meters
<b>Conformance</b>	
Approvals	EN 55022 Class A, FCC Part 15 Class A
Standard warranty	2 years repair or replace
<b>Sustainable Offer Status</b>	
RoHS	Compliant
REACH	REACH: Contains No SVHCs
PEP	Available in Documentation tab
EOLI	Available in Documentation tab
Battery Directive	Compliant