

Share:







BR1000G-IN



Description: High Performance Computer and Electronics UPS for Premium Power Protection
Includes : Telephone Cable , USB cable , User Manual , Warranty card

Product Support

-  [User Manual](#)
-  [Replacement Battery](#)
-  [Software & Firmware](#)
- [Product Registration](#)
-  [Product FAQs](#)


[Product Overview](#)

[Technical Specifications](#)

[Documentation](#)

[Software & Firmware](#)

Output

[Print Technical Specification](#) 

Output power capacity	600Watts / 1.0 kVA
Max Configurable Power (Watts)	600Watts / 1.0 kVA
Nominal Output Voltage	230V
Efficiency at Full Load	84.0 %
Output Frequency (sync to mains)	50/60 Hz +/-1 Hz
Topology	Line Interactive
Waveform type	Stepped approximation to a sine wave
Transfer Time	8ms typical : 12ms maximum

Input

Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	India 3-pin 6A
Cord Length	1.52meters
Input voltage range for main operations	150 - 280 V
Number of Power Cords	1
Efficiency at Full Load	84.0 %

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	7.4hour(s)
Expected Battery Life (years)	2 - 4
RBC Quantity	1
Extendable Run Time	1
Extended Run Options	APC-Power-Saving-Back-UPS-Pro-1000-with-LCD-230V-India
Runtime	View Runtime Graph View Runtime Chart

Communications & Management

Interface Port(s)	USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Surge Protection and Filtering	
Surge energy rating	680Joules
Data Line Protection	Analog phone line for phone/fax/modem/DSL (RJ-11 connector), Network line - 10/100/1000 Base-T Ethernet (RJ-45 connector)
Physical	
Maximum Height	301mm , 30.1CM
Maximum Width	114mm , 11.4CM
Maximum Depth	382mm , 38.2CM
Net Weight	11.35KG
Shipping weight	12.77KG
Shipping Height	381mm , 38.1CM
Shipping Width	229mm , 22.9CM
Shipping Depth	483mm , 48.3CM
Color	Black
Master Carton Units	2.0
Master Carton Weight	27.2
Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	45.0dBA
Conformance	
Standard warranty	2 years repair or replace
Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs