



BR1000-IN has not been replaced. Please contact your customer care centre for more information.

ⓘ Discontinued

Overview

Model Name	APC Back-UPS RS, 1000VA, 230V, INDIA
Includes	CD with software , Cord management straps , USB cable , User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Bangladesh , India , Sri Lanka

Output

Output Power Capacity	600 Watts / 1000 VA
Max Configurable Power (Watts)	600 Watts / 1000 VA
Nominal Output Voltage	230V
Nominal Output Voltage	Line Interactive
Output Connections	(2) India 2/3-pin 6A (Surge Protection) , (3) India 2/3-pin 6A (Battery Backup)

Input

Nominal Input Voltage	230V
Input Frequency	47 - 63 Hz
Input Connections	Indian/South African BS 546A
Cord Length	1.98 meters
Input voltage range for main operations	175 - 295 V
Input voltage adjustable range for mains operation	160 - 286V

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	1
Typical recharge time	15 hour(s)
Replacement Battery	RBC33
RBC Quantity	1

Communications & Management

Interface Port(s)	USB
-------------------	-----

Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rating	180 Joules
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Data Line Protection	Analog phone line for phone/fax/modem/DSL (RJ-11 connector) , Network line - 10/100 Base-T Ethernet (RJ-45 connector)

Physical

Maximum Height	371.0 mm
Maximum Width	86.0 mm
Maximum Depth	333.0 mm
Rack Height	2 U
Net Weight	10.61 kg
Shipping Weight	11.82 kg
Shipping Height	455.0 mm
Shipping Width	203.0 mm
Shipping Depth	416.0 mm
Master Carton Units	1.0
Color	Beige
Units per Pallet	20.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-5 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.000 dB
Online Thermal Dissipation	180.000 BTU/hr

Conformance

Approvals	CE
Standard warranty	2 years repair or replace
Equipment protection policy	Lifetime : 100000 Euro