



BR1500-IN has not been replaced. Please contact your customer care center for more information.

ⓘ Discontinued

### Overview

Model Name	APC Back-UPS 1500VA, 230V, India
Includes	CD with software , Cord management straps , Free trial of anti-virus : firewall : email privacy : system recovery and online backup software , USB cable , User Manual
Standard Lead Time	Usually in Stock
Product Distribution	India

### Output

Output Power Capacity	865 Watts / 1500 VA
Max Configurable Power (Watts)	865 Watts / 1500 VA
Nominal Output Voltage	230V
Nominal Output Voltage	Line Interactive
Waveform Type	Stepped approximation to a sinewave
Output Connections	(2) India 2/3-pin 6A (Surge Protection) , (3) India 2/3-pin 6A (Battery Backup)

### Input

Nominal Input Voltage	230V
Input Frequency	47 - 63 Hz
Input Connections	Indian/South African BS 546A
Cord Length	1.98 meters
Input voltage range for main operations	175 - 295 V
Input voltage adjustable range for mains operation	160 - 286V

### Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	1
Typical recharge time	8 hour(s)
Replacement Battery	RBC33
RBC Quantity	1

## Communications & Management

Interface Port(s)	USB
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

Surge energy rating	180 Joules
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Data Line Protection	Analog phone line for phone/fax/modem/DSL (RJ-11 connector) , Network line - 10/100 Base-T Ethernet (RJ-45 connector)

## Physical

Maximum Height	371.0 mm
Maximum Width	86.0 mm
Maximum Depth	333.0 mm
Rack Height	2 U
Net Weight	11.59 kg
Shipping Weight	12.82 kg
Shipping Height	455.0 mm
Shipping Width	203.0 mm
Shipping Depth	417.0 mm
Master Carton Units	1.0
Color	Beige
Units per Pallet	20.0

## Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-5 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.000 dB
Online Thermal Dissipation	180.000 BTU/hr

## Conformance

Approvals	CE
Standard warranty	2 years repair or replace
Equipment protection policy	Lifetime : 100000 Euro