

Share:



BX600C-IN

Description: Battery Backup & Surge Protector for Electronics and Computers
Includes : User Manual , Warranty card



Product Support

- [User Manual](#)
- [Replacement Battery](#)
- [Product Registration](#)
- [Product FAQs](#)

[Product Overview](#)

[Technical Specifications](#)

[Documentation](#)

[Options](#)

Output

[Print Technical Specification](#)

Output power capacity	360Watts / 600VA
Max Configurable Power (Watts)	360Watts / 600VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	47 - 63 Hz
Topology	Line Interactive
Waveform type	Stepped approximation to a sine wave

Input

Nominal Input Voltage	230V
Input frequency	47 - 63 Hz
Input Connections	India 3-pin 6A
Cord Length	1.22meters
Input voltage range for main operations	145 - 290V
Number of Power Cords	1

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	8hour(s)
Replacement Battery	APCRBC110
Runtime	View Runtime Manual Table

Communications & Management

Control panel	LED status display with On Line : On Battery : Replace Battery and Building Wiring Fault
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	255Joules
---------------------	-----------

Physical

Maximum Height	218mm , 21.8CM
Maximum Width	107mm , 10.7CM
Maximum Depth	237mm , 23.7CM
Net Weight	4.7KG
Shipping weight	5.2KG
Shipping Height	295mm , 29.5CM
Shipping Width	165mm , 16.5CM
Shipping Depth	310mm , 31.0CM

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters

Conformance

Approvals	BIS Approved
Standard warranty	2 years repair or replace

Sustainable Offer Status

REACH	REACH: Contains No SVHCs
-------	--------------------------