



# APC Smart-UPS RC 3000VA, 230V, no battery, LCD, 2x IEC 60320 C13 outlets

**SRC3KUXI**

Call for More Information 18001030011

- Includes: Basic UPS signalling RS-232 cable, Installation guide, User manual

Output	
Output power capacity	2.4kWatts / 3.0kVA
Max Configurable Power (Watts)	2.4kWatts / 3.0kVA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Efficiency at Full Load	93.0 %
Output Voltage Distortion	Less than 3 %
Output Frequency (sync to mains)	50 Hz +/- 0.1 % For 50 Hz nominal Unsynchronised, 50/60 Hz +/- 3 Hz Sync to mains, 60 Hz +/- 0.1 % For 60 Hz nominal Unsynchronised
Other Output Voltages	220 V, 240 V
Load Crest Factor	3 : 1
Topology	Double conversion online
Waveform type	Sine wave
Output Connections	(2) IEC 60320 C13 (1) Hard wire 3-wire (H N + E)
Output Voltage THD	< 3% linear load
Transfer Time	4 ms typical
Bypass	Built-in bypass

Input	
Nominal Input Voltage	230V
Input frequency	40 - 70 Hz
Input Connections	Hard wire 3-wire (1P + N + E)

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

Input	
Input voltage range for main operations	140 - 280V
Efficiency at Full Load	93.0 %

Batteries & Runtime	
Battery type	External battery system
Replacement battery cartridge note	72V. SMF or Flooded battery compatible. Internal charger 2A - 13A programmable

Communications & Management	
Control panel	Multifunction LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering	
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical	
Maximum Height	432MM, 43.2CM
Maximum Width	85MM, 8.5CM
Maximum Depth	483MM, 48.3CM
Net Weight	11.5KG
Shipping weight	14.5KG
Shipping Height	575MM, 57.5CM
Shipping Width	265MM, 26.5CM
Shipping Depth	585MM, 58.5CM

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	0 - 45 °C

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

APC Smart-UPS RC 3000VA, 230V, no battery, LCD, 2x IEC 60320 C13 outlets | SRC3KUXI | Downloaded on 01/11/2022 (EST)

Environmental	
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 4572meters
Audible noise at 1 meter from surface of unit	55.0dBA

Conformance	
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.