



APC Smart-UPS RC 6000VA, 230V, no battery, LCD

SRCE6KUXI

Call for More Information 18001030011

- Includes: Smart UPS signalling RS-232 cable, User manual

Output	
Output power capacity	5.4kWatts / 6.0kVA
Max Configurable Power (Watts)	5.4kWatts / 6.0kVA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 5 %
Other Output Voltages	220 V, 240 V
Topology	Double conversion online
Waveform type	Sine wave
Output Connections	(1) Hard wire 3-wire (H N + E)
Bypass	Built-in static bypass

Input	
Nominal Input Voltage	230V
Input frequency	40 - 70 Hz
Input Connections	Hard wire 3-wire
Input voltage range for main operations	160 - 285V

Batteries & Runtime	
Battery type	External battery system

Communications & Management	
Control panel	Multifunction LCD status and control console

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Communications & Management

Audible Alarm Audible and visible alarms : configurable delays

Emergency Power Off (EPO) Yes

Available SmartSlot™ Interface Quantity 1

Surge Protection and Filtering

Surge energy rating 480Joules

Filtering Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping
response time : meets UL 1449

Physical

Maximum Height 476MM, 47.6CM

Maximum Width 135MM, 13.5CM

Maximum Depth 706MM, 70.6CM

Net Weight 18.71KG

Shipping weight 23.45KG

Shipping Height 570MM, 57.0CM

Shipping Width 275MM, 27.5CM

Shipping Depth 790MM, 79.0CM

Environmental

Operating Temperature 0 - 40 °C

Operating Relative Humidity 0 - 95 %

Operating Elevation 0 - 914.4meters

Storage Temperature -15 - 65 °C

Storage Relative Humidity 0 - 95 %

Storage Elevation 0 - 3048meters

Audible noise at 1 meter from surface of unit 55.0dBA

Conformance

Standard warranty 2 years repair or replace

Technical Specifications

APC Smart-UPS RC 6000VA, 230V, no battery, LCD | SRCE6KUXI | Downloaded on 01/11/2022 (EST)

Sustainable Offer Status

RoHS

Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.