

Share:



SUA1500I-IN



Description: Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Includes : CD with software , Smart UPS signalling RS-232 cable , USB cable , User Manual



Product Support

- User Manual
- Replacement Battery
- Software & Firmware
- Product Registration
- Product FAQs

Product Overview

Technical Specifications

Documentation

Software & Firmware

Options

Output

Print Technical Specification

Output power capacity	980Watts / 1.5 kVA
Max Configurable Power (Watts)	980Watts / 1.5 kVA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 5%
Output Frequency (sync to mains)	47 - 53 Hz for 50 Hz nominal, 57 - 63 Hz for 60 Hz nominal
Topology	Line Interactive
Waveform type	Sine wave

Output Connections
 (8) IEC 320 C13 (Battery Backup)
 (2) IEC Jumpers (Battery Backup)

Input

Nominal Input Voltage	230V
Input frequency	50 Hz +/- 3 Hz
Input Connections	IEC-320 C14
Input voltage range for main operations	160 - 286V
Input voltage adjustable range for mains operation	151 - 302V

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3hour(s)
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Runtime	View Runtime Graph View Runtime Chart

Communications & Management

Interface Port(s)	DB-9 RS-232 , SmartSlot , USB
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Surge Protection and Filtering	
Surge energy rating	480Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
Physical	
Maximum Height	216mm , 21.6CM
Maximum Width	170mm , 17.0CM
Maximum Depth	439mm , 43.9CM
Net Weight	24.09KG
Shipping weight	26.82KG
Shipping Height	370mm , 37.0CM
Shipping Width	330mm , 33.0CM
Shipping Depth	590mm , 59.0CM
Units per Pallet	24.0
Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 40 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	45.0dBA
Online thermal dissipation	135.0BTU/hr
Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs