

**CP- UNW-HP24G2F2-24****24 Port PoE Switch****Main Features**

- Support PoE, PoE+ , Hi-PoE
- Red port support Hi-PoE, can be used with the PoE extender
- 250 meters long distance PoE transmission
- PoE management, PoE Setting/Event Statistics/Green PoE
- Layer 2 management PoE switch
- Support Web management
- PoE budget: 240W
- High lightning protection design
- Non-blocking video transmission

# CP- UNW-HP24G2F2-24

## 24 Port PoE Switch

### Feature

Switch Capacity  
Packet Forwarding Rate  
MAC Address List  
Ethernet Port  
PoE Power Consumption  
PoE Power Budget  
PoE Protocol  
VLAN  
Lightning Protection  
Spanning Tree  
Flow Control  
Port Aggregation  
Mirroring  
Long Distance Mode  
QoS  
Security Features  
System Maintenance  
Network Management  
PoE Management  
DHCP  
Power Source  
Operating Temperature  
Humidity  
Weight  
Dimensions

### Specification

8.8G  
6.55Mpps  
4K  
2 x 10/100/1000 Base-T (Combo port), 2 x 1000 Base-X (Combo port), 24 x 10/100 Base-T (PoE power supply)  
Port1/2 support Hi-PoE (60W), PoE+, PoE Each power  $\leq 30W$  Total  $\leq 240W$   
240W  
IEEE802.3af, IEEE802.3at, Hi-PoE  
802.1Q Standard VLAN  
Common Mode 4KV Differential Mode 2V  
STP RSTP  
Half-duplex based on back pressure type control; Full duplex based on PAUSE frame  
Static link aggregation LACP protocol  
Many-to-one port mirroring  
"Power & Data" transmission distance up to 250m  
High and low priority, WRR 802.1P, DSCP Support priority according to protocol  
IP+MAC binding based on port; IEEE802.1x port authentication  
One-key recovery Support the updated packet upload System log  
WEB (http and https protocol) Support SNMP V1/V2C/V3  
PoE setting (real-time port consumption), PoE event statistics, Green PoE  
Support DHCP-Client  
AC 100~240V  
-10°C~+55°C  
10%~90%  
3.51kg  
440mm x 300mm x 44mm