

R195669 Loose Tube Armored Outdoor LSZH, OM4, 6-fibers

030.1422 Similar product

**Description**

The outdoor cable for applications in harsh conditions. It contains a central gel-filled loose tube of a diameter of $2/2.8 \pm 0.1$ mm for 2 - 16 fibers or 3.5 mm for 18 - 24 fibers. The outer sheath is made of a 0.155 mm ECCS armor plus a 1.8 mm LSZH sheath.

Sheath: LSZH, black.

Fiber: multimode (MM) G50/125.

Weight

0.000G

Technical Data

Standardisation	IEC 60794-1-2 E1; IEC 60794-1-2 E11; IEC 60794-1-2 E3; IEC 60794-1-2 F1; IEC 60794-1-2 E4; IEC 60794-1-2 E7; IEC 60794-1-2 E10
Cable class	Loose Tube
Cable design	A-D(ZN)W2Y
Fiber class	OM4
Number of fibers / conductors	6
Cable jacket material	LSZH
Cable jacket characteristics	water-tight
Tensile strength	800N
Cable protection	ECCS tape, steel armoring
Cable overall diameter	8.5 ± 1.2 mm
Crush resistance	2000N
Fiber / conductor diameter	G50/125 μ m
Fiber type	Multimode (MM)
Color	black
Length (meter)	2000
