

Patch Cord Cat.6, U/UTP, 4P, LSZH, Green, RJ45/u - RJ45/u

**DESCRIPTION**

Cable Identification : U/UTP
Outer Jacket : LSZH
Outer Diameter : 5.0 ± 0.5 mm
Weight : 78.000 ± 6.0 G

TECHNICAL DATA

Standardisation	Compliant with Cat.6 requirements of ISO/IEC 11801, EN 50173, EN 50168 and EIA/TIA 568.C.x
Cable Class	Patch Cord
Connector Class	Connector
Connector Type	RJ45
Protection Class IP	IP20
Category	Cat.6
Cu Cable Shielding	U/UTP
Min. Bend Radius	4 x O.D.
Dielectric Withstanding Voltage	1000VAC, 1min. (60Hz)
Insulation Resistance	500 MO (min.)
Current Rating	1.5A (Max.) @ 25°C
Cable Shielding	U/UTP
Number of Conductors	8
Stranding	4 X 2P Cable
Jacket Material	LSZH
Cable Jacket Characteristics	Cable, Metal-Free
Cable Overall Diameter	5.0 ± 0.5 mm
Conductor Size	24 AWG (26/7)
Conductor Type	Stranded Conductor
Color	Cable Green

Patch Cord Cat.6, U/UTP, 4P, LSZH, Green, RJ45/u - RJ45/u

Description	Part Code
Patch Cord Cat.6, U/UTP, 4P, LSZH, GR, RJ45/u - RJ45/u, 1 Mtrs	R196169
Patch Cord Cat.6, U/UTP, 4P, LSZH, GR, RJ45/u - RJ45/u, 2 Mtrs	R196108
Patch Cord Cat.6, U/UTP, 4P, LSZH, GR, RJ45/u - RJ45/u, 3 Mtrs	R196139
Patch Cord Cat.6, U/UTP, 4P, LSZH, GR, RJ45/u - RJ45/u, 5 Mtrs	R196140
Patch Cord Cat.6, U/UTP, 4P, LSZH, GR, RJ45/u - RJ45/u, 10 Mtrs	R195627