



(Photo is just for reference)

24F Rack Mount fiber Shelf LCPC DX MM

Scope of supply:

- 19" 1U FMS 1 pc
- LC-PC DX Adapters MM 12 pc
- Splice Trays 1 pc
- 19" 1U Rack mount set 1 pc
- Kit 'B' 1 pcs
- Test Reports
- Instruction Manual

Description	PU	Product-No.
19" 1U Rack Mount Fiber Shelf loaded with LC-PC DX - 24F	1	R220043

Product description

The 19" 1U Fiber Shelf is a shelf assembly for a fiber management system in a networking rack environment. This system utilizes the same proven fiber routing procedures. The result is consistent, high quality fiber management throughout the network.

Features

- Easy removable Top plate with push buttons
- Inner tray of patch panel can be easily slide front & back
- Splice elements for up to 12x LC-PC DX MM adapters
- Stress free and easy to handle fiber guidance
- High degree of flexibility and modularity
- Fast, secure and time saving installation and fiber routing
- Modular and flexible for splicing & patching applications

Technical Data

Criteria	Date / Value	
1U Patch panel	Material Color	CRCA 1.2mm, powder coated RAL 7035
Splice Tray	Material Color	Plastic, ABS/PC
Weight [kgs]	net Packed	4.5 5.0
Dimensions [mm]	W x D x H	482 x 270 x 44.5
Temperature range [°C]	Transport Storage Operation	-40 up to +85 -40 up to +85 -25 up to +55

Standards

Description	Standard
Climate testing	IEC 60068-2-2 / IEC 60068-2-1
Temperature change and damp heat	IEC 61300-2-22 / IEC 61300-2-19