

## OVERVIEW

Basic Upgradeable rPDUs provide reliable power distribution to critical IT equipment within a rack or cabinet.

### Benefits

- With the Geist Upgradeable hot-swap technology, users may easily transform basic rPDUs to metered or monitored PDUs with the addition of the appropriate Interchangeable Monitoring Device (IMD).
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard five-year limited warranty.



## Part #: G110092

**Model Number:** MG01X4B0-36CF13-2PS56B2A10-S-A

**Category:** Basic

**Sub Category:** Upgradeable

**Power Configuration:** 16A, 230/400V WYE, 11.0kW

**Physical Configuration:** 66in / 1683mm, Vertical

### Product Summary:

rPDU, Basic Upgradeable, 16A, 230/400V WYE, 11.0kW, Vertical, (36) Combination C13/C19, 10ft power cord with 3P+N+E (IP44), Black Powder Coat.

### Monitoring:


No Monitoring (Upgradeable with IMD module)

### Plug Form:



3P+N+E (IP44)

### Receptacle:



Combination C13/C19  
(Quantity: 36)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

|                    |                                             |
|--------------------|---------------------------------------------|
| Monitoring         | No Monitoring (Upgradeable with IMD module) |
| Quantity Of Inputs | 1                                           |
| Voltage            | 200-240/346-415V WYE                        |

|                                                              |                                                      |
|--------------------------------------------------------------|------------------------------------------------------|
| <b>Current</b>                                               | 16A x 3 Phase WYE                                    |
| <b>VA per Input (Load Capacity)</b>                          | 11.0kW (230V)                                        |
| <b>Frequency</b>                                             | 50/60Hz                                              |
| <b>Over Current Protection</b>                               | None                                                 |
| <b>Switch</b>                                                | No                                                   |
| <b>Power Cable Wire Gauge</b>                                | 2.5mmÂ² H07RN-F                                      |
| <b>Power Cable Length</b>                                    | 10ft / 3m                                            |
| <b>Power Entry Location</b>                                  | Bottom Front                                         |
| <b>Plug Type</b>                                             | IEC60309 3P + N + E, 16A, 230/400V, Splashproof IP44 |
| <b>Receptacle/Socket Type #1</b>                             | Combination C13/C19                                  |
| <b>- Quantity on Face</b>                                    | 36                                                   |
| <b>- Quantity per Phase</b>                                  | 12                                                   |
| <b>- Circuit Color ID</b>                                    | 3 Circuit = Orange, Green, Blue                      |
| <b>- Style</b>                                               | Banks of 6                                           |
| <b>- Voltage per Receptacle/Socket</b>                       | 230V                                                 |
| <b>Maximum Operating Temperature</b>                         | 60C / 140F                                           |
| <b>Heavy Steel - Powder Coat Finish</b>                      | Black                                                |
| <b>Configuration</b>                                         | Zero U                                               |
| <b>7938 Vertical Mounting Bracket Kit</b>                    | Yes                                                  |
| <b>Toolless Mounting Hardware - Center to Center Spacing</b> | 61.25in and 64.75in / 1556mm and 1645mm              |
| <b>Product Warranty</b>                                      | 5-year limited warranty                              |
| <b>Certification/Agency Approvals</b>                        | CE Marked                                            |
| <b>Certification/Agency Approvals</b>                        | UKCA Marked                                          |
| <b>Certification/Agency Approvals</b>                        | Complies with IEC 62368-1 (DOC Available)            |
| <b>Certification/Agency Approvals</b>                        | Complies with EN 55032 and EN 55035                  |
| <b>Certification/Agency Approvals</b>                        | RoHS Compliant                                       |
| <b>Certification/Agency Approvals</b>                        | RCM Mark (EMC Only)                                  |
| <b>Certification/Agency Approvals</b>                        | China RoHS                                           |
| <b>Chassis Dimensions (LxWxD)</b>                            | 66.25in x 2in x 2in / 1683mm x 51mm x 51mm           |
| <b>Shipped Weight</b>                                        | 16lbs (7.26kg)                                       |