

FIBER-OPTIC PATCH-CORDS SINGLEMODE DUPLEX

Datasheet



Patch-cord SM DX LCPC-LCPC

Scope of supply:

- Patch-Cord
- Test report printed on P/N Label

1 pc

TECHNICAL DATA

Duplex Cable

Criteria		Value	Standard
Cable ø [mm]		2.0 (± 0.1)	
Material		LSZH	
Secondary coating	Diameter [µm] Material	900 (± 5%) LSZH	
Nominal weight [kg/km]		3.7	
Temperature range [°C]	Storage Installation Operation	-25 up to +60 -10 up to + 50 -20 up to + 60	IEC 61300-2-22
Maximum tensile strength [mm]	Installation Operation	200 100	IEC 60794-1-2 E1
Minimum bending radius [mm]	Installation Operation	50 25	IEC 60794-1-2 E11
Compressive strength [N/10cm]	Short term Permanent	250 100	IEC 60794-1-2 E13
Heat of combustion [MJ/m]		0.08	

Fiber Types Available

Description	ISO/IEC 11801	IEC 60793-2-50/10	ITU-T	EIA/TIA
Singlemode SM (PC and APC polishing)	OS 2	B1.3	G.652.D	492CAAB
	---	B6_a1	G.657.A1	---
	---	B6_a2	G.657.A2	---
	---	B6_b2	G.657.B2	---
	---	B6_b3	G.657.B3	---

Optical Properties (as per IEC 61753-1)

Description		Grade B/2	Grade C/2	Grade D/3
Insertion loss IL [dB]	97%	≤ 0.25	≤ 0.50	≤ 1.00
	Typical value	≤ 0.12	≤ 0.25	≤ 0.50
Return loss RL [dB]	97%	≥ 45	≥ 45	≥ 35
	Typical value	≥ 55	≥ 55	≥ 45

FIBER-OPTIC PATCH-CORDS SINGLEMODE DUPLEX

Datasheet

Mechanical Properties

Criteria		Value	Standard
Mating durability [times]		500x (minimum)	IEC 61300-2-2
Retention [N / s]	Cable Pigtail	100 / 120 5 / 60	IEC 61300-2-4
Vibration		10-55Hz, 1 octave / min. 3 axis of 15 cycles, 0.5h / axis amplitude 0.75 mm	IEC 61300-2-1
Repeated bending [100 Cycles]	Cable Pigtail	Load 5N (-90° / 0° / +90° / 0°C Load 0.2N (-90° / 0° / +90° / 0°C)	IEC 61300-2-44
Static side load [N / min]	Cable Pigtail	1 / 60 0.2 / 5	IEC 61300-2-42
Drop [m]		1.5 (5 times)	IEC 61300-2-12

Part Numbers P/N

P/N	Description	P/N	Description
R225337	PC-DX-LCPC-LCPC-C/2-2SM-OS2-0.3M	R198240	PC-DX-LCPC-LCPC-C/2-2SM-OS2-25.0M
R198080	PC-DX-LCPC-LCPC-C/2-2SM-OS2-0.5M	R226642	PC-DX-LCPC-LCPC-C/2-2SM-OS2-28.0M
R198103	PC-DX-LCPC-LCPC-C/2-2SM-OS2-1.0M	R198087	PC-DX-LCPC-LCPC-C/2-2SM-OS2-30.0M
R222212	PC-DX-LCPC-LCPC-C/2-2SM-OS2-1.5M	R198361	PC-DX-LCPC-LCPC-C/2-2SM-OS2-35.0M
R198235	PC-DX-LCPC-LCPC-C/2-2SM-OS2-2.0M	R198124	PC-DX-LCPC-LCPC-C/2-2SM-OS2-40.0M
R223648	PC-DX-LCPC-LCPC-C/2-2SM-OS2-2.5M	R198358	PC-DX-LCPC-LCPC-C/2-2SM-OS2-45.0M
R198236	PC-DX-LCPC-LCPC-C/2-2SM-OS2-3.0M	R198239	PC-DX-LCPC-LCPC-C/2-2SM-OS2-50.0M
R198241	PC-DX-LCPC-LCPC-C/2-2SM-OS2-5.0M	R198471	PC-DX-LCPC-LCPC-C/2-2SM-OS2-55.0M
R222809	PC-DX-LCPC-LCPC-C/2-2SM-OS2-6.0M	R198440	PC-DX-LCPC-LCPC-C/2-2SM-OS2-60.0M
R198121	PC-DX-LCPC-LCPC-C/2-2SM-OS2-7.0M	R198472	PC-DX-LCPC-LCPC-C/2-2SM-OS2-65.0M
R222810	PC-DX-LCPC-LCPC-C/2-2SM-OS2-7.5M	R198441	PC-DX-LCPC-LCPC-C/2-2SM-OS2-70.0M
R198370	PC-DX-LCPC-LCPC-C/2-2SM-OS2-8.0M	R198473	PC-DX-LCPC-LCPC-C/2-2SM-OS2-75.0M
R198339	PC-DX-LCPC-LCPC-C/2-2SM-OS2-9.0M	R198442	PC-DX-LCPC-LCPC-C/2-2SM-OS2-80.0M
R198002	PC-DX-LCPC-LCPC-C/2-2SM-OS2-10.0M	R198474	PC-DX-LCPC-LCPC-C/2-2SM-OS2-85.0M
R198043	PC-DX-LCPC-LCPC-C/2-2SM-OS2-12.0M	R198443	PC-DX-LCPC-LCPC-C/2-2SM-OS2-90.0M
R198018	PC-DX-LCPC-LCPC-C/2-2SM-OS2-15.0M	R198475	PC-DX-LCPC-LCPC-C/2-2SM-OS2-95.0M
R222520	PC-DX-LCPC-LCPC-C/2-2SM-OS2-16.0M	R198444	PC-DX-LCPC-LCPC-C/2-2SM-OS2-100.0M
R222389	PC-DX-LCPC-LCPC-C/2-2SM-OS2-18.0M	R226553	PC-DX-LCPC-LCPC-C/2-2SM-OS2-110.0M
R198122	PC-DX-LCPC-LCPC-C/2-2SM-OS2-20.0M	R224234	PC-DX-LCPC-LCPC-C/2-2SM-OS2-120.0M
R222830	PC-DX-LCPC-LCPC-C/2-2SM-OS2-22.0M	R224235	PC-DX-LCPC-LCPC-C/2-2SM-OS2-130.0M
R222831	PC-DX-LCPC-LCPC-C/2-2SM-OS2-24.0M	R222555	PC-DX-LCPC-LCPC-C/2-2SM-OS2-150.0M