PANACAST SPEAKERMIC

Flexible audio expansion device for larger meeting spaces

› For medium and large rooms

Technical Specifications

General info	Box contents	PanaCast SpeakerMic, Mounting plate, SpeakerMic Adapter, 3x table adhesive, Installation leaflet
	Packaging dimensions (WxHxD)	67mm x 186mm x 140mm | 2.64in x 7.32in x 5.51in
	Main unit dimensions (ØxH)	136mm x 55mm | 5.35in x 2.17in
	Materials used	Fabric, Aluminium, Black plastic
	Main unit weight	623g | 22oz
	USB cable length	0.5m | 1.6ft
	IP rating (main unit)	IPX2
	Warranty	2 years
Audio	Number of microphones	4
	Microphone type	Omnidirectional
	Microphone frequency range	Analog 100Hz - 18000Hz | Digital 100Hz - 18000Hz
	Microphone bandwidth	100Hz - 18000Hz
	Noise reduction on calls	Yes
	Speaker size	60mm | 2.36in
	Speaker frequency range	100Hz - 18000Hz
	Speaker bandwidth (music mode)	100Hz - 18000Hz
	Speaker bandwidth (speak mode)	100Hz - 18000Hz
Software & Apps	Compatible software and/or apps	Jabra Plus, Cloud service provider including Microsoft Teams Admin Center and Zoom Device Management
Connectivity	Connectivity	Cat6 (not included), RJ45, RJ45 to USB-C (SpeakerMic Adapter)
	Maximum cable length	Up to 30 meters
Extended info	Operating temperature	0°C to 40°C | 32°F to 104°F
	Storage temperature	-20°C to 45°C | -4°F to 113°F

	SKU	Description
Products	8900-100	Jabra PanaCast SpeakerMic
Accessories	14307-61	SpeakerMic Grommet Mount

PanaCast SpeakerMic Datasheet 25022026

Download the latest version of this document at:
jabra.com/support

© 2026 GN Hearing A/S. All rights reserved.Jabra® is a registered trademark of GN Hearing A/S.
The Bluetooth® word mark and logos are registered trademarks owned by
Bluetooth SIG, Inc. and any use of such marks by GN Hearing A/S is under license.
Specifications are subject to change without notice.