

Product datasheet

Specifications



APC NetShelter Basic Rack PDU,
0U/1U, 120-240V/15A, 220-240V/
10A, 8 C13 outlet

AP6015A

Main

Product or component type	PDU
Main Input Voltage	100 V 120 V 200 V 208 V 230 V 240 V
Input current limits	15 A
Network frequency	50/60 Hz
Main Output Voltage	100 V 120 V 200 V 208 V 230 V 240 V
Input Connection Type	IEC 60320 C14
Number of power socket outlets	8 IEC 60320 C13
Load capacity	2300 VA
[In] rated current	12 A
permissible voltage	100...240 V
Max current draw	15 A
Max line current	15 A
PDU type	Basic
Number of rack unit	1U
Provided equipment	Installation guide Safety guide

Complementary

Mounting location	Front Rear
Mounting mode	Not rack-mountable
Mounting position	Horizontal
Height	237 mm
Width	44 mm
Depth	76 mm
Net weight	0.91 kg

Environmental

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	cUL listed CE EAC IRAM UL listed VDE
------------------------	---

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	28.6 cm
Package 1 Width	13 cm
Package 1 Length	21 cm
Package 1 Weight	1.37 kg
SCC14	10731304327797

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	2 101 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	2 096 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds

Use Again



Repack and remanufacture

Recyclability potential, in %	45
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

