

Product datasheet

Specifications



APC NetShelter SX, Networking Rack Enclosure, 48U, Black, 2258H x 750W x 1200D mm

AR3347

Overview

Presentation	NetShelter SX Networking Enclosure expands Schneider Electric's superior IT enclosure line with improved support for high density networking applications. Integrated high density cable managers and improved cable access roof provide support for large cable bundles. When combined with the Side Airflow Duct Kit, the Networking Enclosure ensures complete isolation of cold intake and hot exhaust air for large switches and SAN directors.
--------------	--

Main

Product or component type	Rack enclosure
Number of rack unit	48U
Rack width	19"
Permanent permissible load	1020.6 kg dynamic 1701.0 kg static
Provided equipment	Baying hardware Key(s) Keyed-alike doors and side panels Leveling feet Mounting hardware Pre-installed casters Side panels Vertical cable managers

Complementary

Mounting mode	Not rack-mountable
Minimum mounting depth	279.4 mm
Maximum mounting depth	958.9 mm
Colour	Black
Marking	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 16 gauge rear door 18 gauge roof 18 gauge side panels
Height	2258 mm
Width	750 mm
Depth	1200 mm
Net weight	185.45 kg

Environmental

Standards	UL 2416 UL 60950-1 EIA-310E
-----------	-----------------------------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	238.500 cm
Package 1 Width	85.100 cm
Package 1 Length	132.100 cm
Package 1 Weight	208.180 kg

Contractual warranty

Warranty (in months)	60
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	731 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	697 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	18 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	16 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Again

 Repack and remanufacture	
Recyclability potential, in %	95
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative















