

Product datasheet

Specifications



APC NetShelter Soundproof, Server Rack Enclosure, 12U, Maple

AR4012A

Main

Product or component type	Rack enclosure
Number of rack unit	12U
Rack width	19"
Permanent permissible load	840 kg static
Provided equipment	Casters

Complementary

Mounting mode	Not rack-mountable
Minimum mounting depth	690 mm
Maximum mounting depth	830 mm
Colour	Maple
Height	785 mm
Width	750 mm
Depth	1130.4 mm
Net weight	114 kg

Environmental

Standards	EIA-310D
-----------	----------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	100.33 cm
Package 1 Width	87.63 cm
Package 1 Length	134.62 cm
Package 1 Weight	157.3 kg

Contractual warranty

Warranty (in months)	24
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	554 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	529 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	13 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	12 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Again

 Repack and remanufacture	
Recyclability potential, in %	95
End of life manual availability	No need of specific recycling operations
Take-back	No

Image of product / Alternate images

Alternative





